

Package: RARfreq (via r-universe)

September 5, 2024

Type Package

Title Response Adaptive Randomization with 'Frequentist' Approaches

Version 0.1.5

Description Provides functions and command-line user interface to generate allocation sequence by response-adaptive randomization for clinical trials. The package currently supports two families of frequentist response-adaptive randomization procedures, Doubly Adaptive Biased Coin Design ('DBCD') and Sequential Estimation-adjusted Urn Model ('SEU'), for binary and normal endpoints. One-sided proportion (or mean) difference and Chi-square (or 'ANOVA') hypothesis testing methods are also available in the package to facilitate the inference for treatment effect. Additionally, the package provides comprehensive and efficient tools to allow one to evaluate and compare the performance of randomization procedures and tests based on various criteria. For example, plots for relationship among assumed treatment effects, sample size, and power are provided. Five allocation functions for 'DBCD' and six addition rule functions for 'SEU' are implemented to target allocations such as 'Neyman', 'Rosenberger' Rosenberger et al. (2001) <doi:10.1111/j.0006-341X.2001.00909.x> and 'Urn' allocations.

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

Imports dplyr, ggplot2, latex2exp, magrittr, patchwork, stats, tidyr, data.table, reshape2, Rdpack

RdMacros Rdpack

Suggests spelling, testthat (>= 3.0.0)

Config/testthat/edition 3

Language en-US

NeedsCompilation no

Author Mengjia Yu [aut], Xiu Huang [aut, cre], Li Wang [aut], Hongjian Zhu [aut]

Maintainer Xiu Huang <xiu.huang@aya.yale.edu>

Date/Publication 2024-05-07 12:40:03 UTC

Repository <https://hoyden0329.r-universe.dev>

RemoteUrl <https://github.com/cran/RARfreq>

RemoteRef HEAD

RemoteSha 05f4a09455c56609ef253c6adba9c95f0806af79

Contents

DBCD_BINARY	2
DBCD_BINARY_raw	3
DBCD_GAUSSIAN	5
DBCD_GAUSSIAN_raw	6
power_comparison_Power_vs_n	7
power_comparison_Power_vs_n_GAUSSIAN	8
power_comparison_Power_vs_Trt	10
power_comparison_Power_vs_Trt_GAUSSIAN	12
SEU_BINARY_raw	13
SEU_GAUSSIAN_raw	15
SEU_power_comparison_Power_vs_n	16
SEU_power_comparison_Power_vs_n_GAUSSIAN	17
SEU_power_comparison_Power_vs_Trt	19
SEU_power_comparison_Power_vs_Trt_GAUSSIAN	21
SEU_simulation_main	23
SEU_simulation_main_GAUSSIAN	24
simulation_main	26
simulation_main_GAUSSIAN	28
Index	31

DBCD_BINARY

Doubly Adaptive Biased Coin Design (Binary Responses)

Description

Allocates patients to one of treatments based on doubly adaptive biased coin design on summary level data.

Usage

DBCD_BINARY(S_RK, N_RK, group_allo, rho_func_index, rho_func, alpha)

Arguments

S_RK	A vector of current success rates for each treatment arm.
N_RK	A vector of current enrolled subjects in each arm. The length must be the same as 'S_RK'.
group_allo	An integer of the size of group allocation. The default is 1.
rho_func_index	Supply a number of 1, 2 or 3 indicting the allocation function to use. 1 = Wei's allocation; 2 = Neyman allocation; 3 = Rosenberger allocation. The default is 3.
rho_func	Supply a user-specified allocation function of S_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.

Details

'DBCD_BINARY' assigns the next subject to a group given the observed success rates, enrolled subjects and allocation function.

Value

Number of the arm that the next subject is assigned to.

Examples

```
# There are 3 arms each of which receives 25 patients.
# The observed response rates are 40%, 28% and 60%, respectively.
# The following command returns the number of arm that the next patient will
# be assigned to.
DBCD_BINARY(S_RK = c(0.4, 0.28, 0.6),
            N_RK = c(25, 25, 25),
            rho_func_index = 3, alpha=2)

# Urn allocation
DBCD_BINARY(S_RK = c(0.4, 0.3),
            N_RK = c(25, 25),
            group_allo = 1,
            rho_func_index = NULL,
            rho_func = function(x) rev(1-x)/sum(1-x),
            alpha=2)
```

DBCD_BINARY_raw

Doubly Adaptive Biased Coin Design (Binary Data Frame)

Description

Allocates patients to one of treatments based on doubly adaptive biased coin design on individual data.

Usage

```
DBCD_BINARY_raw(X.df, group_allo, rho_func_index, rho_func, alpha)
```

Arguments

<code>X.df</code>	A data frame of two columns: treatment arm and response value.
<code>group_allo</code>	An integer of the size of group allocation. The default is 1.
<code>rho_func_index</code>	Supply a number of 1, 2 or 3 indicating the allocation function to use. 1 = Wei's allocation 2 = Neyman allocation; 3 = Rosenberger allocation. The default is 3.
<code>rho_func</code>	Supply a user-specified allocation function of sample response rates when <code>rho_func_index</code> is NULL. Default is NULL.
<code>alpha</code>	Supply a number indicating the subscripts of the probability function. The default is 2.

Details

'DBCD_BINARY_raw' assigns the next subject to a group given the observed success rates, enrolled subjects and allocation function.

Value

Code of the arm that the next subject is assigned to.

Examples

```
X.df = data.frame(
  ARM = sample(LETTERS[1:3],50,replace = TRUE),
  RESPONSE = sample(c(0,1),50,replace = TRUE)
)
DBCD_BINARY_raw(X.df, rho_func_index = 3, alpha=2)
```

```
X.df = data.frame(
  ARM = sample(LETTERS[1:2],40,replace = TRUE),
  RESPONSE = sample(c(0,1),40,replace = TRUE)
)
DBCD_BINARY_raw(
  X.df, rho_func_index = NULL,
  rho_func = function(x) rev(1-x)/sum(1-x), alpha=2
)
```

DBCD_GAUSSIAN

*Doubly Adaptive Biased Coin Design (Gaussian Responses)***Description**

Allocates patients to one of treatments based on doubly adaptive biased coin design on summarized data.

Usage

```
DBCD_GAUSSIAN(Mean_RK,SD_RK, N_RK, group_allo, rho_func_index,
rho_func, alpha)
```

Arguments

Mean_RK	A vector of current response means for each treatment arm.
SD_RK	A vector of current response standard deviations for each treatment arm.
N_RK	A vector of current enrolled subjects in each arm. The length must be the same as 'Mean_RK'.
group_allo	An integer of the size of group allocation. The default is 1.
rho_func_index	Supply a number of 1 or 2 indicting the allocation function to use. 1 = Zhang-Rosenberger allocation; 2 = Neyman allocation. The default is 2.
rho_func	Supply a user-specified allocation function of Mean_RK and SD_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.

Details

'DBCD_GAUSSIAN' assigns the next subject to a group given the observed success rates, enrolled subjects and allocation function.

Value

Number of the arm that the next subject is assigned to.

Examples

```
# There are 2 arms each of which receives 10 patients.
# The observed response means are 4.5 and 5, respectively.
# The following command returns the number of arm that the next patient will
# be assigned to.
DBCD_GAUSSIAN(Mean_RK = c(4.5,5),
SD_RK = c(1.32,0.72),
N_RK = c(10,10),
rho_func_index = 2, alpha=2)
```

```

DBCD_GAUSSIAN(Mean_RK = c(4.5,5),
SD_RK = c(1.32,0.72),
N_RK = c(10,10),
rho_func_index = 1, alpha=2)

```

DBCD_GAUSSIAN_raw *Doubly Adaptive Biased Coin Design (Gaussian Responses)*

Description

Allocates patients to one of treatments based on doubly adaptive biased coin design on summarized data.

Usage

```
DBCD_GAUSSIAN_raw(X.df, group_allo, rho_func_index, rho_func, alpha)
```

Arguments

<code>X.df</code>	A data frame of two columns: treatment arm and response value.
<code>group_allo</code>	An integer of the size of group allocation. The default is 1.
<code>rho_func_index</code>	Supply a number of 1, 2 or 3 indicating the allocation function to use. (TODO: add reference) 1 = Zhang-Rosenberger allocation; 2 = Neyman allocation. The default is 2.
<code>rho_func</code>	Supply a user-specified allocation function of Mean_RK and SD_RK when <code>rho_func_index</code> is NULL. Default is NULL.
<code>alpha</code>	Supply a number indicating the subscripts of the probability function. The default is 2. (Hu and Zhang 2004)

Details

'DBCD_GAUSSIAN' assigns the next subject to a group given the observed success rates, enrolled subjects and allocation function.

Value

Number of the arm that the next subject is assigned to.

References

Hu F, Zhang L (2004). "Asymptotic Properties of Doubly Adaptive Biased Coin Designs for Multitreatment Clinical Trials." *The Annals of Statistics*. doi: [10.1214/aos/1079120137](https://doi.org/10.1214/aos/1079120137).

Examples

```
X.df = data.frame(
  ARM = sample(LETTERS[1:2],50,replace = TRUE),
  RESPONSE = rnorm(50)
)

DBCD_GAUSSIAN_raw(X.df)
```

power_comparison_Power_vs_n

Comparison of Powers for Different Tests under Different DBCD Randomization Methods (Binary Responses)

Description

Compares the power of tests under different sample sizes for the same treatment effect and design through matrices and plots.

Usage

```
power_comparison_Power_vs_n(n_seq, nstart_seq, p, nstop_mat,
  replication, group_allo, rho_func_index, rho_func, alpha, sig_level)
```

Arguments

n_seq	A sequence of numbers of patients. The default is c(50, 100, 150, 200).
nstart_seq	The burn-in sample size of each arm. If NULL, n_seq/20 will be used.
p	A vector of probabilities containing probabilities for each treatment arm (where the first element refers to the control arm). The length of p should correspond to the number of treatment arms. The default is p = c(0.3, 0.3, 0.6).
nstop_mat	A matrix of sample size stopping caps for each arm. Each row corresponds to each n in n_seq, and each column represents each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. The group_allo will be applied to all n (from each n_seq). Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
rho_func_index	Supply a number of 1, 2 or 3 indicting the allocation function to use. 1 = Wei's allocation 2 = Neyman allocation; 3 (default) = Rosenberger allocation.

rho_func	Supply a user-specified allocation function of S_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.
sig_level	Significant level. The default is 0.05.

Details

'power_comparison_Power_vs_n' reads different sample sizes as well as the corresponding burn-in size and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of the estimators of treatment effect
- Power_chisq - Average power of Chi-square test
- Power_oneside - Average power of one-sided Welch T-test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Four figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test, 4) Power of one-sided proportion test

Examples

```
## Default setting
power_comparison_Power_vs_n(
  n_seq = seq(from = 50, to = 200, by = 50),
  nstart_seq = round(seq(from = 50, to = 200, by = 50) / 20),
  p = c(0.3, 0.3, 0.6),
  nstop_mat = NULL,
  replication = 5,
  group_allo = 1,
  rho_func_index = 3,
  rho_func = NULL,
  alpha = 2,
  sig_level = 0.05
)
```

power_comparison_Power_vs_n_GAUSSIAN

Comparison of Powers for Different Tests under Different DBCD Randomization Methods (Gaussian Responses)

Description

Compares the power of tests under different sample sizes for the same treatment effects and design through matrices and plots.

Usage

```
power_comparison_Power_vs_n_GAUSSIAN(n_seq, nstart_seq, mu, sd,
nstop_mat, replication, group_allo, rho_func_index, rho_func, alpha,
sig_level)
```

Arguments

n_seq	A sequence of numbers of patients. The default is c(50, 100, 150, 200).
nstart_seq	burn-in sample size of each arm. If NULL, n_seq/20 will be used.
mu	A vector of mean response for each treatment arm (where the first element refers to the control arm). The length of mu should correspond to the number of arms. The default is mu = c(4.5,5).
sd	A vector of response standard deviations for each treatment arm. (where the first element refers to the control arm). The length of sd should correspond to the number of arms. The default is sd = c(1.32, 0.72).
nstop_mat	A matrix of sample size stopping caps for each arm. Each row corresponds to each n in n_seq, and each column represents each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. The group_allo will be applied to all n (from each n_seq). Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
rho_func_index	Supply a number of 1 or 2 indicting the allocation function to use. 1 = Zhang-Rosenberger allocation; 2 (default) = Neyman allocation.
rho_func	Supply a user-specified allocation function of Mean_RK and SD_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.
sig_level	Significant level. The default is 0.05.

Details

'power_comparison_Power_vs_n_GAUSSIAN' reads different sample sizes as well as the corresponding burn-in size and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power_oneside - Average power of one-sided Welch T-test performed for each of the k-th arm against H0: $\mu_1 > \mu_k$ without multiplicity adjustment

- Power_aov - Average power of ANOVA test
- Plot - Four figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of ANOVA test, 4) Power of one-sided Welch T-test

Examples

```
## Default setting
power_comparison_Power_vs_n_GAUSSIAN(
  n_seq = seq(from = 50, to = 200, by = 50),
  nstart_seq = round(seq(from = 50, to = 200, by = 50) / 20),
  mu = c(4.5,5),
  sd = c(1.32,0.72),
  nstop_mat = NULL,
  replication = 5,
  group_allo = 1,
  rho_func_index = 2,
  rho_func = NULL,
  alpha = 2,
  sig_level = 0.05
)
```

power_comparison_Power_vs_Trt

*Comparison of Powers for Treatment Effects under Different DBCD
Randomization Methods (Binary Responses)*

Description

Compares the power of a 2-arm design under different treatment effects for the same sample size and placebo effect through matrices and plots.

Usage

```
power_comparison_Power_vs_Trt(n, nstart, p_pbo, p_trt, nstop,
  replication, group_allo, rho_func_index, rho_func, alpha, sig_level)
```

Arguments

n	The number of patients. The default is 100.
nstart	Burn-in sample size of each arm. The default is n/20.
p_pbo	Success rate of placebo (control) arm. The default is 0.3.
p_trt	A vector containing success rates of treatment arm.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.

replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
rho_func_index	Supply a number of 1, 2 or 3 indicting the allocation function to use. 1 = Wei's allocation 2 = Neyman allocation; 3 (default) = Rosenberger allocation;
rho_func	Supply a user-specified allocation function of Mean_RK and SD_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.
sig_level	Significant level. The default is 0.05.

Details

'power_comparison_Power_vs_Trtr' reads different treatment effects and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power - Average power: 1) Chi-square test, 2) one-sided proportion test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Three figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test and power of one-sided proportion test

Examples

```
## Default setting
power_comparison_Power_vs_Trtr(
  n = 100,
  nstart = round(100/20),
  p_pbo = 0.3,
  p_trt = seq(0,0.3,0.1)+0.3,
  nstop = NULL,
  replication = 5,
  group_allo = 1,
  rho_func_index = 3,
  rho_func = NULL,
  alpha = 2,
  sig_level = 0.05
)
```

power_comparison_Power_vs_Tr_t_GAUSSIAN

*Comparison of Powers for Treatment Effects under Different DBCD
Randomization methods (Gaussian Responses)*

Description

Compares the power of a 2-arm design under different treatment effects for the same sample size and placebo effect through matrices and plots.

Usage

```
power_comparison_Power_vs_Tr_t_GAUSSIAN(n, nstart, mu_pbo, sd_pbo,
mu_trt, sd_trt, nstop, replication, group_allo, rho_func_index, rho_func,
alpha, sig_level)
```

Arguments

n	The number of patients. Default is 100.
nstart	Burn-in sample size of each arm. Default is n/20.
mu_pbo	Mean response of placebo (control) arm. Default is 4.5.
sd_pbo	Response standard deviation of placebo (control) arm. Default is 1.32.
mu_trt	A vector containing mean responses of treatment.
sd_trt	A vector containing response standard deviations of treatment.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
rho_func_index	Supply a number of 1 or 2 indicating the allocation function to use. 1 = Zhang-Rosenberger allocation (2-arm allocation only); 2 (default) = Neyman allocation.
rho_func	Supply a user-specified allocation function of Mean_RK and SD_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. Default is 2.
sig_level	Significant level. Default is 0.05.

Details

'power_comparison_Power_vs_Trт_GAUSSIAN' reads different treatment effects and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power - Average power: 1) ANOVA test, 2) one-sided Welch T-test performed for each of the k-th arm against $H_0: \mu_1 > \mu_k$ without multiplicity adjustment
- Plot - Three figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of ANOVA test and power of one-sided Welch T-test

Examples

```
## Default setting
power_comparison_Power_vs_Trт_GAUSSIAN(
n = 100,
nstart = round(100/20),
mu_pbo = 4.5,
sd_pbo = 1.32,
mu_trt = seq(0,0.6,0.2)+4.5,
sd_trt = rep(1.32,4),
nstop = NULL,
replication = 5,
group_allo = 1,
rho_func_index = 2,
rho_func = NULL,
alpha = 2,
sig_level = 0.05
)
```

SEU_BINARY_raw

Sequential Estimation-adjusted Urn Model (Binary Data)

Description

Allocates patients to one of treatments based on sequential estimation-adjusted urn model (SEU) on summarized data.

Usage

```
SEU_BINARY_raw(x.df, urn_comp, arms, group_allo, add_rule_index,
add_rule)
```

Arguments

<code>x.df</code>	A data frame of two columns: treatment arm and response value.
<code>urn_comp</code>	A vector of current urn composition.
<code>arms</code>	A vector of arm names. If it is not provided, the arms occurred in <code>x.df</code> will be assumed as all possible arms. Suggest to always assign arms.
<code>group_allo</code>	An integer of the size of group allocation. The default is 1.
<code>add_rule_index</code>	Supply a number of 1, 2 or 3 indicting the addition rules to target allocation functions. 1 = randomized play-the-winner (RPW) rule that targets the urn allocation 2 = the SEU model that targets Neyman allocation; 3 = the SEU model that targets Rosenberger allocation; 4 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
<code>add_rule</code>	Supply a user-specified addition rules function of <code>x.df</code> and <code>arms</code> when <code>add_rule_index</code> is NULL. Default is NULL.

Details

'SEU_BINARY_raw' assigns the next subject to a group given the observed data, current urn composition, full list of arm codes, number of group allocation and addition rule function.

Value

Code of arms that the next group of subjects assigned to and the updated urn composition.

Examples

```
x.df = data.frame(
  ARM = sample(LETTERS[1:3],50,replace = TRUE),
  RESPONSE = sample(c(0,1),50,replace = TRUE)
)
SEU_BINARY_raw(x.df, urn_comp=c(0,0,0), arms=c("A","B","C"))
```

```
x.df = data.frame(
  ARM = sample(LETTERS[1:2],40,replace = TRUE),
  RESPONSE = sample(c(0,1),40,replace = TRUE)
)
SEU_BINARY_raw(x.df,
  urn_comp=c(0,0),
  arms=c("A","B"),
  group_allo = 1,
  add_rule_index = 3)
```

SEU_GAUSSIAN_raw *Sequential Estimation-adjusted Urn Model (Gaussian Responses)*

Description

Allocates patients to one of treatments based on sequential estimation-adjusted urn model (SEU) on summarized data.

Usage

```
SEU_GAUSSIAN_raw(x.df, urn_comp, arms, group_allo,
  add_rule_index, add_rule)
```

Arguments

x.df	A data frame of two columns: treatment arm and response value. treatment arm.
urn_comp	A vector of current urn composition.
arms	A vector of arm names. If it is not provided, the arms occurred in x.df will be assumed as all possible arms. Suggest to always assign arms.
group_allo	An integer of the size of group allocation. The default is 1.
add_rule_index	Supply a number of 1 or 2 indicting the addition rules to target allocation functions. 1 = the SEU model targeting Neyman allocation; 2 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL.

Details

'SEU_GAUSSIAN' assigns the next subject to a group given the observed success rates, enrolled subjects and allocation function.

Value

Number of the arm that the next subject is assigned to.

Examples

```
x.df = data.frame(
  ARM = sample(LETTERS[1:2],50,replace = TRUE),
  RESPONSE = rnorm(50)
)

SEU_GAUSSIAN_raw(x.df,
  urn_comp=c(0,0),
  arms=c("A","B"),
  group_allo = 1,
  add_rule_index = 1)
```

 SEU_power_comparison_Power_vs_n

Comparison of Powers for Sample Sizes under Different SEU Randomization Methods (Binary Responses)

Description

Compares the power of tests under different sample sizes for the same treatment effects and design through matrices and plots.

Usage

```
SEU_power_comparison_Power_vs_n(n_seq, nstart_seq, p, urn_comp,
nstop_mat, replication, group_allo, add_rule_index, add_rule, add_rule_full,
sig_level)
```

Arguments

n_seq	A sequence of settings' number of patients. The default is c(50, 100, 150, 200).
nstart_seq	The burn-in sample size of each arm. The default is n_seq/20 = c(2, 5, 8, 10).
p	A vector of probabilities containing probabilities for each treatment arm (where the first element refers to the control arm). The length of p should correspond to the number of treatment arms. The default is p = c(0.3, 0.3, 0.6).
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.
nstop_mat	A matrix of sample size stopping caps for each arm. Each row corresponds to each n in n_seq, and each column represents each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. The group_allo will be applied to all n (from each n_seq). Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1, 2 or 3 indicting the addition rules to target allocation functions. 1 = randomized play-the-winner (RPW) rule that targets the urn allocation 2 = the SEU model that targets Neyman allocation; 3 = the SEU model that targets Rosenberger allocation;' 4 = the SEU model that assigns probability of 0.6+1/K to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_BINARY_raw for details on x.df and arms.)

- `add_rule_full` Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is FALSE for `add_rule_index=1` and TRUE otherwise.
- `sig_level` Significant level (one-sided). The default is 0.05.

Details

'SEU_power_comparison_Power_vs_n' reads different sample sizes as well as the corresponding burn-in size and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power_chisq - Average power of Chi-square test
- Power_oneside - Average power of one-sided Welch T-test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Four figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test, 4) Power of one-sided proportion test

Examples

```
## Default setting
SEU_power_comparison_Power_vs_n(
  n_seq = seq(from = 50, to = 200, by = 50),
  nstart_seq = round(seq(from = 50, to = 200, by = 50) / 20),
  p = c(0.3, 0.3, 0.6),
  urn_comp = NULL,
  nstop_mat = NULL,
  replication = 4,
  group_allo = 1,
  add_rule_index = 1,
  add_rule = NULL,
  add_rule_full = FALSE,
  sig_level = 0.05
)
```

SEU_power_comparison_Power_vs_n_GAUSSIAN

Comparison of Powers for Sample Sizes under Different SEU Randomization Methods (Gaussian Responses)

Description

Compares the power of tests under different sample sizes for the same treatment effects and design through matrices and plots.

Usage

```
SEU_power_comparison_Power_vs_n_GAUSSIAN(n_seq, nstart_seq, mu, sd,
  urn_comp, nstop_mat, replication, group_allo, add_rule_index, add_rule,
  add_rule_full, sig_level)
```

Arguments

n_seq	A sequence of settings' number of patients. The default is c(50, 100, 150, 200).
nstart_seq	The burn-in sample size of each arm. The default is n_seq/20 = c(2, 5, 8, 10).
mu	A vector of mean response for each treatment arm (where the first element refers to the control arm). The length of mu should correspond to the number of arms. The default is mu = c(4.5,5).
sd	A vector of response standard deviations for each treatment arm. (where the first element refers to the control arm). The length of sd should correspond to the number of arms. The default is sd = c(1.32, 0.72).
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.
nstop_mat	A matrix of sample size stopping caps for each arm. Each row corresponds to each n in n_seq, and each column represents each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. The group_allo will be applied to all n (from each n_seq). Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1 or 2 indicting the addition rules to target allocation functions. 1 = the SEU model targeting Neyman allocation; 2 = the SEU model that assigns probability of 0.6+1/K to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_GAUSSIAN_raw for details on x.df and arms.)
add_rule_full	Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is TRUE.
sig_level	Significant level (one-sided). The default is 0.05.

Details

'SEU_power_comparison_Power_vs_n_GAUSSIAN' reads different sample sizes as well as the corresponding burn-in size and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power_chisq - Average power of Chi-square test
- Power_oneside - Average power of one-sided Welch T-test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Four figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test, 4) Power of one-sided proportion test

Examples

```
## Default setting
SEU_power_comparison_Power_vs_n_GAUSSIAN(
n_seq = seq(from = 50, to = 100, by = 50),
nstart_seq = round(seq(from = 50, to = 100, by = 50) / 20),
mu = c(4.5,5),
sd = c(1.32,0.72),
urn_comp = NULL,
nstop_mat = NULL,
replication = 5,
group_allo = 1,
add_rule_index = 1,
add_rule = NULL,
add_rule_full = NULL,
sig_level = 0.05
)
```

SEU_power_comparison_Power_vs_Trtr

Comparison of Powers for Treatment Effects under Different SEU Randomization Methods (Binary Responses)

Description

Compares the power of a 2-arm design under different treatment effects for the same sample size and placebo effect through matrices and plots.

Usage

```
SEU_power_comparison_Power_vs_Trtr(n, nstart, p_pbo, p_trt, urn_comp,
nstop, replication, group_allo, add_rule_index, add_rule, add_rule_full,
sig_level)
```

Arguments

n	The number of patients. The default is 100.
nstart	Burn-in sample size of each arm. The default is n/20.
p_pbo	Success rate of placebo (control) arm. The default is 0.3.
p_trt	A vector containing success rates of treatment arm.
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1, 2 or 3 indicting the addition rules to target allocation functions. 1 = randomized play-the-winner (RPW) rule that targets the urn allocation 2 = the SEU model that targets Neyman allocation; 3 = the SEU model that targets Rosenberger allocation; 4 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_BINARY_raw for details on x.df and arms.)
add_rule_full	Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is FALSE for add_rule_index=1 and TRUE otherwise.
sig_level	Significant level (one-sided). The default is 0.05.

Details

'SEU_power_comparison_Power_vs_Trtr' reads different treatment effects and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power - Average power: 1) Chi-square test, 2) one-sided proportion test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Three figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test and power of one-sided proportion test

Examples

```
## Default setting
SEU_power_comparison_Power_vs_TrT(
  n = 40,
  nstart = round(40/20),
  p_pbo = 0.3,
  p_trt = seq(0,0.3,0.1)+0.3,
  urn_comp = NULL,
  nstop = NULL,
  replication = 5,
  group_allo = 1,
  add_rule_index = 3,
  add_rule = NULL,
  add_rule_full = FALSE,
  sig_level = 0.05
)
```

```
SEU_power_comparison_Power_vs_TrT_GAUSSIAN
```

Comparison of Powers for Treatment Effects under Different SEU Randomization Methods (Gaussian Responses)

Description

Compares the power of a 2-arm design under different treatment effects for the same sample size and placebo effect through matrices and plots.

Usage

```
SEU_power_comparison_Power_vs_TrT_GAUSSIAN(n, nstart, mu_pbo, sd_pbo,
mu_trt, sd_trt, urn_comp, nstop, replication, group_allo, add_rule_index,
add_rule, add_rule_full, sig_level)
```

Arguments

n	The number of patients. The default is 100.
nstart	Burn-in sample size of each arm. The default is n/20.
mu_pbo	Mean response of placebo (control) arm. Default is 4.5.
sd_pbo	Response standard deviation of placebo (control) arm. Default is 1.32.
mu_trt	A vector containing mean responses of treatment.
sd_trt	A vector containing response standard deviations of treatment.
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.

nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1 or 2 indicting the addition rules to target allocation functions. 1 = the SEU model targeting Neyman allocation; 2 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_GAUSSIAN_raw for details on x.df and arms.)
add_rule_full	Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is TRUE.
sig_level	Significant level (one-sided). The default is 0.05.

Details

'SEU_power_comparison_Power_vs_Tr_t_GAUSSIAN' reads different treatment effects and outputs allocation, estimated rates and powers.

Value

- Allocation - Average and standard deviation (SD) of allocation distribution
- Estimation - Average and standard deviation of treatment effect
- Power - Average power: 1) Chi-square test, 2) one-sided proportion test performed for each of the k-th arm against $H_0: p_1 > p_k$ without multiplicity adjustment
- Plot - Three figures of results: 1) Allocation mean and SD, 2) Estimated mean response and SD, 3) Power of Chi-square test and power of one-sided proportion test

Examples

```
## Default setting
SEU_power_comparison_Power_vs_Tr_t_GAUSSIAN(
n = 40,
nstart = round(40/20),
urn_comp = NULL,
nstop = NULL,
replication = 5,
group_allo = 1,
add_rule_index = 1,
add_rule = NULL,
add_rule_full = TRUE,
```

```
sig_level = 0.05
)
```

SEU_simulation_main *Sequential Estimation-adjusted Urn Model with Simulated Data (Binary Data)*

Description

Allocates patients to one of treatments based on sequential estimation-adjusted urn model (SEU) with simulated data.

Usage

```
SEU_simulation_main(n, nstart, p, urn_comp, nstop, replication, group_allo,
  add_rule_index, add_rule, add_rule_full, sig_level)
```

Arguments

n	The number of patients. The default is 500.
nstart	Burn-in sample size of each arm. The default is $n/20$.
p	A vector containing response probabilities for each treatment arm (where the first element refers to the control arm). The length of p should correspond to the number of arms. The default is $p = c(0.3, 0.3, 0.6)$.
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1, 2 or 3 indicting the addition rules to target allocation functions. 1 = randomized play-the-winner (RPW) rule that targets the urn allocation 2 = the SEU model that targets Neyman allocation; 3 = the SEU model that targets Rosenberger allocation; 4 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_BINARY_raw for details on x.df and arms.)

- add_rule_full Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is FALSE for add_rule_index=1 and TRUE otherwise.
- sig_level Significant level (one-sided). The default is 0.05.

Details

'SEU_simulation_main' can sample response and adaptively randomize subjects group by group.

Value

- allocation_mean - Average of allocation in each arm based on 'replication' repeats
- allocation_sd - Standard deviation of allocation in each arm based on 'replication' repeats
- SS_mean - Average of sample size in each arm based on 'replication' repeats
- SS_sd - Standard deviation of sample size in each arm based on 'replication' repeats
- power_chisq - Average power of chi-square test.
- power_oneside - Average power for each of the k-th arm to perform one-sided test against $H_0: p_1 > p_k$ without multiplicity adjustment
- p_estimate_mean - Average of estimated success rate p
- p_estimate_sd - Standard deviation of estimated success rate p

Examples

```
## Default method
SEU_simulation_main(n = 500,
  nstart = round(500 / 20),
  p = c(0.3, 0.3, 0.6),
  nstop=c(500,500,500),
  urn_comp = c(0,0,0),
  replication = 5,
  group_allo = 1,
  add_rule_index = 1,
  add_rule_full = FALSE,
  sig_level = 0.05
)
```

SEU_simulation_main_GAUSSIAN

*Sequential Estimation-adjusted Urn Model with Simulated Data
(Gaussian Responses)*

Description

Allocates patients to one of treatments based on sequential estimation-adjusted urn model (SEU) with simulated data.

Usage

```
SEU_simulation_main_GAUSSIAN(n, nstart, mu, sd, urn_comp, nstop,
  replication, group_allo, add_rule_index, add_rule,
  add_rule_full, sig_level)
```

Arguments

n	The number of patients. The default is 500.
nstart	Burn-in sample size of each arm. The default is $n/20$.
mu	A vector of mean response for each treatment arm (where the first element refers to the control arm). The length of mu should correspond to the number of arms. The default is $\mu = c(4.5, 5)$.
sd	A vector of response standard deviations for each treatment arm. (where the first element refers to the control arm). The length of sd should correspond to the number of arms. The default is $sd = c(1.32, 0.72)$.
urn_comp	A vector of current urn composition. The default is NULL, which indicates no ball in the urn.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
add_rule_index	Supply a number of 1 or 2 indicting the addition rules to target allocation functions. 1 = the SEU model targeting Neyman allocation; 2 = the SEU model that assigns probability of $0.6+1/K$ to winner at each step. The default is 1.
add_rule	Supply a user-specified addition rules function of x.df and arms when add_rule_index is NULL. Default is NULL. (See SEU_GAUSSIAN_raw for details on x.df and arms.)
add_rule_full	Indicator of reference data for updating addition rule. If TRUE, the addition rule is updated by full observation at each group allocation. If FALSE, the addition rule is updated by each group observation. The default is TRUE.
sig_level	Significant level (one-sided). The default is 0.05.

Details

'SEU_simulation_main_GAUSSIAN' can sample response and adaptively randomize subjects group by group.

Value

- allocation_mean - Average of allocation in each arm based on ‘replication’ repeats.
- allocation_sd - Standard deviation of allocation in each arm based on ‘replication’ repeats.
- SS_mean - Average of sample size in each arm based on ‘replication’ repeats.
- SS_sd - Standard deviation of sample size in each arm based on ‘replication’ repeats.
- power_aov - Average power of ANOVA test.
- power_oneside - Average power for each of the k-th arm to perform one-sided Welch T-test against $H_0: \mu_1 > \mu_k$ without multiplicity adjustment.
- mu_estimate_mean - Average of estimated response mean ‘mu’.
- sd_estimate_mean - Average of estimated response standard deviation ‘sd’.
- mu_estimate_sd - Standard deviation of estimated response mean ‘mu’.
- sd_estimate_sd - Standard deviation of estimated response standard deviation ‘sd’.

Examples

```
## Default method
SEU_simulation_main_GAUSSIAN(
n = 50,
nstart = round(50 / 20),
mu = c(4.5,5),
sd = c(1.32,0.72),
urn_comp = c(0,0),
nstop=c(50,50),
replication = 5,
group_allo = 1,
add_rule_index = 1,
add_rule = NULL,
add_rule_full = TRUE,
sig_level = 0.05
)
```

simulation_main	<i>Doubly Adaptive Biased Coin Design with Simulated Data (Binary Responses)</i>
-----------------	--

Description

Allocates patients to one of treatments based on the doubly adaptive biased coin design with simulated data.

Usage

```
simulation_main(n, nstart, p, nstop, replication, group_allo, rho_func_index,
rho_func, alpha, sig_level)
```

Arguments

n	The number of patients. The default is 500.
nstart	Burn-in sample size of each arm. The default is n/20.
p	A vector containing response probabilities for each treatment arm (where the first element refers to the control arm). The length of p should correspond to the number of arms. The default is $p = c(0.3, 0.3, 0.6)$.
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.
group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as $group_allo = seq(nstart*length(p)+1,n)$.
rho_func_index	Supply a number of 1, 2 or 3 indicting the allocation function to use; default to 3. * 1 = Wei's allocation (Urn allocation); * 2 = Neyman allocation; * 3 (default) = Rosenberger allocation;
rho_func	Supply a user-specified allocation function of S_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.
sig_level	Significant level (one-sided). The default is 0.05.

Details

'simulation_main' can sample response and adaptively randomize subjects group by group.

Value

- allocation_mean - Average of allocation in each arm based on 'replication' repeats
- allocation_sd - Standard deviation of allocation in each arm based on 'replication' repeats
- SS_mean - Average of sample size in each arm based on 'replication' repeats
- SS_sd - Standard deviation of sample size in each arm based on 'replication' repeats
- power_chisq - Average power of chi-square test.
- power_oneside - Average power for each of the k-th arm to perform one-sided test against $H_0: p_1 > p_k$ without multiplicity adjustment
- p_estimate_mean - Average of estimated success rate p
- p_estimate_sd - Standard deviation of estimated success rate p

Examples

```

## Default method
simulation_main(n = 500,
nstart = round(500 / 20),
p = c(0.3, 0.3, 0.6),
nstop=c(500,500,500),
replication = 5,
group_allo = 1,
rho_func_index = 3,
alpha = 2,
sig_level = 0.05
)

```

simulation_main_GAUSSIAN

Doubly Adaptive Biased Coin Design with Simulated Data (Gaussian Responses)

Description

Allocates patients to one of treatments based on the doubly adaptive biased coin design with simulated data.

Usage

```

simulation_main_GAUSSIAN(n, nstart, mu, sd, nstop, replication, group_allo,
rho_func_index, rho_func, alpha, sig_level)

```

Arguments

n	The number of patients. The default is 500.
nstart	Burn-in sample size of each arm. The default is n/20.
mu	A vector of mean response for each treatment arm (where the first element refers to the control arm). The length of mu should correspond to the number of arms. The default is mu = c(4.5,5).
sd	A vector of response standard deviations for each treatment arm. (where the first element refers to the control arm). The length of sd should correspond to the number of arms. The default is sd = c(1.32, 0.72).
nstop	A vector of stopping cap of sample size for each arm. The trial stops if at least one arm reaches the corresponding cap. The default is NULL, which means no cap.
replication	the number of replications of the simulation. The default is 100.

group_allo	A number or a vector of group size(s) for allocation. If a number is given, the allocation ratios will be updated for each batch of group_allo samples. If a vector is given, the allocation ratios will be updated sequentially in group according to the vector. Any value greater than n will be omitted. The default is group_allo=1, which is the same as group_allo = seq(nstart*length(p)+1,n).
rho_func_index	Supply a number of 1 or 2 indicating the allocation function to use. 1 = Zhang-Rosenberger allocation (2-arm allocation only); 2 (default) = Neyman allocation.
rho_func	Supply a user-specified allocation function of Mean_RK and SD_RK when rho_func_index is NULL. Default is NULL.
alpha	Supply a number indicating the subscripts of the probability function. The default is 2.
sig_level	Significant level. The default is 0.05.

Details

'simulation_main_GAUSSIAN' can sample response and adaptively randomize subjects group by group.

Value

- allocation_mean - Average of allocation in each arm based on 'replication' repeats.
- allocation_sd - Standard deviation of allocation in each arm based on 'replication' repeats.
- SS_mean - Average of sample size in each arm based on 'replication' repeats.
- SS_sd - Standard deviation of sample size in each arm based on 'replication' repeats.
- power_aov - Average power of ANOVA test.
- power_oneside - Average power for each of the k-th arm to perform one-sided Welch T-test against $H_0: \mu_1 > \mu_k$ without multiplicity adjustment.
- mu_estimate_mean - Average of estimated response mean 'mu'.
- sd_estimate_mean - Average of estimated response standard deviation 'sd'.
- mu_estimate_sd - Standard deviation of estimated response mean 'mu'.
- sd_estimate_sd - Standard deviation of estimated response standard deviation 'sd'.

Examples

```
## Default method
simulation_main_GAUSSIAN(
  n = 500,
  nstart = round(500 / 20),
  mu = c(4.5,5),
  sd = c(1.32,0.72),
  nstop=c(500,500),
  replication = 5,
  group_allo = 1,
  rho_func_index = 2,
  rho_func = NULL,
```

```
alpha = 2,  
sig_level = 0.05  
)
```

Index

DBCD_BINARY, [2](#)
DBCD_BINARY_raw, [3](#)
DBCD_GAUSSIAN, [5](#)
DBCD_GAUSSIAN_raw, [6](#)

power_comparison_Power_vs_n, [7](#)
power_comparison_Power_vs_n_GAUSSIAN,
[8](#)
power_comparison_Power_vs_Trtr, [10](#)
power_comparison_Power_vs_Trtr_GAUSSIAN,
[12](#)

SEU_BINARY_raw, [13](#)
SEU_GAUSSIAN_raw, [15](#)
SEU_power_comparison_Power_vs_n, [16](#)
SEU_power_comparison_Power_vs_n_GAUSSIAN,
[17](#)
SEU_power_comparison_Power_vs_Trtr, [19](#)
SEU_power_comparison_Power_vs_Trtr_GAUSSIAN,
[21](#)
SEU_simulation_main, [23](#)
SEU_simulation_main_GAUSSIAN, [24](#)
simulation_main, [26](#)
simulation_main_GAUSSIAN, [28](#)